



207.02


**PRIVILEGE**  
Latest Technology in:  
K - ANTI-SCRATCHING - N - ANTI-FOGGING

**GreenBag**  
Certified Sustainable Polybag

207.01

**wecustom**  
Digital platform for your custom PPE

**Adapta**  
PROGRAM

 Headform: 1-S / 1-M / 1-L

 EN ISO 16321-1:2022

 28gr.

## Compact Pro - Ref. 207

Safety glasses developed in Bio-Balance polyamide with modern, lightweight and ergonomic design.





 **BIO-BALANCE**

 **DIELECTRIC**

 **DESIGN**

 **2 SIZES**

## CUSTOM PRESCRIPTION







| Versions  | Ref.   | Frame Marking  | Headform  |
|---|--------|--|-----------|
|  Transparent/Blue   | 207.01 | 16321 $\text{\textcircled{T}}$ U1.2 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$    | 1-S       |
|  Grey               | 207.02 | 16321 $\text{\textcircled{T}}$ U1.2 G3 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$ | 1-S       |
|  Transparent / Blue | 207.03 | 16321 $\text{\textcircled{T}}$ U1.2 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$    | 1-M / 1-L |
|  Grey               | 207.04 | 16321 $\text{\textcircled{T}}$ U1.2 G3 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$ | 1-M / 1-L |

| Lens material | Lens marking   | Monofocal     | Progressive             |
|---------------|--|---------------|-------------------------|
| Polycarbonate | $\text{\textcircled{T}}$ C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$ | -12.50, +7.50 | -14.00, +6.00 add.+3.00 |
| Trivex        | $\text{\textcircled{T}}$ C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$ | -14.00, +6.50 | -10.00, +6.00 add.+2.50 |
| Organic 1.5   | $\text{\textcircled{T}}$ $\text{\textcircled{C}}$ $\text{\textcircled{E}}$     | -10.00, +6.00 | -6.00, +6.00 add.+3.00  |
| Organic 1.6   | $\text{\textcircled{T}}$ $\text{\textcircled{C}}$ $\text{\textcircled{E}}$     | -10.00, +7.75 | -9.00, +6.00 add.+3.00  |
| Organic 1.67  | $\text{\textcircled{T}}$ $\text{\textcircled{C}}$ $\text{\textcircled{E}}$     | -14.00, +8.00 | -9.75, +6.50 add.+3.00  |

Bifocal: Only in Organic 1.5, -6.00, +5.75 add.+3.00






| Treatments       | Filters              |
|------------------|----------------------|
| Anti scratch (K) | Ultraviolet (UL1.2)  |
| Anti fog (N)     | Solar (GL3)          |
| Anti reflective  | Photochromic (GL0-3) |
| Water repellent  | Polarized (GL3)      |
| Blue stop        |                      |

## PLANO

| Versions   | Ref.   | Lens marking   | Frame marking   | Use   | Headform  | EAN 13 Unit   | EAN 13 Box    | Box | Carton | Customs code | Technology  |
|--|--------|--|---|---|-----------|---------------|---------------|-----|--------|--------------|---|
|  Clear | 207.05 | $\text{\textcircled{T}}$ UL1.2 1 C T K N $\text{\textcircled{C}}$ $\text{\textcircled{E}}$ | 16321 $\text{\textcircled{T}}$ U1.2 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$ |  | 1-S       | 8445266004676 | 8445266004683 | 21  | 252    | 9004909000   |  |
|  Clear | 207.06 | $\text{\textcircled{T}}$ UL1.2 1 C T K N $\text{\textcircled{C}}$ $\text{\textcircled{E}}$ | 16321 $\text{\textcircled{T}}$ U1.2 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$ |  | 1-M / 1-L | 8445266004690 | 8445266004706 | 21  | 252    | 9004909000   |  |

 Inside  Outside  Welding

## General specifications

| Plano lens material | Frame material  | Frame base  |   |   |   |
|---------------------|---|---|---|---|---|
| Polycarbonate       | BioBased Polyamide  | 4   |   |   |   |
| Measures            |   |   |   |   |   |
| Size:               |  |  |  |  |  |
| Small               | 51 mm   | 35 mm   | 16 mm   | 127 mm  | 138 mm  |
| Large               | 55 mm   | 38 mm   | 15 mm   | 127 mm  | 142 mm  |

## Marked information


| Marked  | Description  |
|---|--|
| $\text{\textcircled{T}}$                          | Identification of OPTOR S.A.U                                  |
| $\text{\textcircled{C}}$ $\text{\textcircled{E}}$ | CE marking   |
| C   | Resistance to high-speed particles, low energy impact (45 m/s) |
| T   | Extreme temperatures   |
| K   | Certified surface deterioration resistance by fine particles   |
| N   | Certified anti-fog resistance                                  |

| Marked | Description   |
|--------|---|
| UL1.2  | UV filter level 1,2 with enhanced color recognition         |
| GL3    | Sunscreen with light signal recognition. Protection class 3 |
| GL0-3  | Photochromic solar filter. Protection class 0-3             |
| 1      | Improved vision   |
| U1.2   | UV filter level 1,2   |



+Info about marking  
Technology and maintenance

[www.pegasosafety.com](http://www.pegasosafety.com)

 [info@pegaso.es](mailto:info@pegaso.es)

Manufacturer: OPTOR S.A.U  
C/Quintana 1 Millars 2-G  
08940 Cornellà de Llobregat  
Barcelona (Spain).