



1095.D5



1095.D5



1095.01




1095.02



 Headform: 1-M

 EN ISO 16321-1:2022, EN ISO 16321-2:2021

 47gr.

## Duplex - Ref. 1095



Gas Welding safety glasses with flip front, developed in nylon with classic design, ergonomic temples and side shields.

 NYLON

 FLIP FRONT

 SIDE SHIELDS

## CUSTOM PRESCRIPTION





Versions	Ref.	Frame Marking	Headform
 Gas Welding DIN3	1095.02	16321 $\text{\textcircled{T}}$ U1.2 W3 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$	1-M
 Gas Welding DIN5	1095.01	16321 $\text{\textcircled{T}}$ U1.2 W5 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$	1-M

Lens material	Lens marking	Monofocal	Progressive
Polycarbonate	$\text{\textcircled{T}}$ C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$	-12.50, +8.75	-14.00, +6.00 add.+3.00
Organic 1.5	$\text{\textcircled{T}}$ $\text{\textcircled{C}}$ $\text{\textcircled{E}}$	-10.00, +8.00	-6.00, +6.00 add.+3.00
Organic 1.6	$\text{\textcircled{T}}$ $\text{\textcircled{C}}$ $\text{\textcircled{E}}$	-10.00, +7.75	-9.00, +6.00 add.+3.25
Trivex	$\text{\textcircled{T}}$ C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$	-10.00, +7.00	-10.00, +6.00 add.+2.50
Organic 1.67	$\text{\textcircled{T}}$ $\text{\textcircled{C}}$ $\text{\textcircled{E}}$	-10.75, +8.00	-9.75, +6.50 add.+3.00

Bifocal: Only in Organic 1.5, -6.00, +5.75 add.+3.00






Treatments	Filters
Anti scratch (K)	Ultraviolet (UL1.2)
Anti fog (N)	
Anti reflective	
Water repellent	
Blue stop	

## PLANO

Versions	Ref.	Lens marking	Frame marking	Use	Headform	EAN 13 Unit	EAN 13 Box	Box	Carton	Customs code	Technology
 Gas Welding DIN3	1095.D3	$\text{\textcircled{T}}$ UL1.2 W3 1 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$	16321 $\text{\textcircled{T}}$ U1.2 W3 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$		1-M	8436010310648	8436010321576	24	288	9004909000	Anti-scratch - Anti-fog
 Gas Welding DIN3	1095.D5	$\text{\textcircled{T}}$ UL1.2 WL5 1 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$	16321 $\text{\textcircled{T}}$ U1.2 W5 C T $\text{\textcircled{C}}$ $\text{\textcircled{E}}$		1-M	8436010312581	8436010313434	21	252	9004909000	Anti-scratch - Anti-fog

 Inside  Outside  Welding

## General specifications

Plano lens material	Frame material	Frame base
Polycarbonate	Polyamide / Nylon / TPR	5
Measures		
Size:	    	
One size	55 mm	50 mm
	18 mm	145 mm
		149 mm

## Marked information


Marked	Description
$\text{\textcircled{T}}$	Identification of OPTOR S.A.U
$\text{\textcircled{C}}$ $\text{\textcircled{E}}$	CE marking
C	Resistance to high-speed particles, low energy impact (45 m/s)
T	Extreme temperatures
K	Certified surface deterioration resistance by fine particles
N	Certified anti-fog resistance

Marked	Description
UL1.2	UV filter level 1,2 with enhanced color recognition
1	Improved vision
W3	Welding filter DIN 3
U1.2	UV filter level 1,2
WL5	Welding filter. Protection class 5
W5	Welding filter DIN 5



+Info about marking  
Technology and maintenance

[www.pegasosafety.com](http://www.pegasosafety.com)

 [info@pegaso.es](mailto:info@pegaso.es)

Manufacturer: OPTOR S.A.U  
C/Quintana 1 Millars 2-G  
08940 Cornellà de Llobregat  
Barcelona (Spain).